

KEY FEATURES



- High Pressure Die Cast Aluminum Body
- With attachment eye or U-Bracket
- Clear or frosted glass cover
- IP 65 - IK08
- 3 sizes available with 8 different wattages
- 2 Different optics
- Colored ring optional
- Built in surge protection device 10kV



Wattage	50W	80W	100W	120W	150W	180W	200W	240W
Instant Lumen Output	6000lm	9600lm	12000lm	14400lm	18000lm	21600lm	24000lm	28800lm
Typical System Efficiency	120lm/W	120lm/W	120lm/W	120lm/W	120lm/W	120lm/W	120lm/W	120lm/W

Typical System Efficiency	> 120 lumen / W		
Color	Warm White (WW)	Neutral White (NW)	Cool White (CW)
Color Temperature	3000K	4000K	5700k
Typical CRI	> 70		
Beam angle	150D / 70D		
Input Voltage	100 - 240V AC		
Frequency	47 - 63 Hz		
Operating Temperature	-30C > +45C		
Storage Temperature	-30C > +60C		
Materials	Die Cast Aluminum Alloy, Optical PC Lens, Clear Flat Glass		
Lifespan	> 100,000 burning hours		

LIGHT DISTRIBUTION



DIMENSIONS

POWER CONSUMPTION	H	Ø	N.W.
50W - 100W	165mm	280mm	2kg
70W - 100W	179mm	320mm	2.6kg
70W - 100W	208mm	400mm	3.6kg

